


1701N

- N type for deep holes
- MT shank
- Extra-long/1
- For ▲ rank items, you may receive until stock exhaustion former edp 2701LS instead of 1701N



P	M	K	N	S	H
★	☆	★	●	●	○

DIN 1870/1	N	HSS OX	SIG 118°	FHA 30°
---------------	---	-----------	----------	---------

DC	DC tol.	MT No.	LCF	OAL	Packaging	EDP no.	Stock
13	0/-0.027	1	205	310	1	P1701N1300N	▲
13.5	0/-0.027	1	220	325	1	P1701N1350N	○
14	0/-0.027	1	220	325	1	P1701N1400N	●
14.5	0/-0.027	2	220	340	1	P1701N1450N	○
15	0/-0.027	2	220	340	1	P1701N1500N	●
15.5	0/-0.027	2	230	355	1	P1701N1550N	○
16	0/-0.027	2	230	355	1	P1701N1600N	●
16.5	0/-0.027	2	230	355	1	P1701N1650N	○
17	0/-0.027	2	230	355	1	P1701N1700N	▲
17.5	0/-0.027	2	245	370	1	P1701N1750N	○
18	0/-0.027	2	245	370	1	P1701N1800N	●
18.5	0/-0.033	2	245	370	1	P1701N1850N	▲
19	0/-0.033	2	245	370	1	P1701N1900N	●
19.5	0/-0.033	2	260	385	1	P1701N1950N	▲
20	0/-0.033	2	260	385	1	P1701N2000N	●
21	0/-0.033	2	260	385	1	P1701N2100N	○
22	0/-0.033	2	270	405	1	P1701N2200N	●
23	0/-0.033	2	270	405	1	P1701N2300N	▲
24	0/-0.033	3	290	440	1	P1701N2400N	▲
25	0/-0.033	3	290	440	1	P1701N2500N	●
26	0/-0.033	3	290	440	1	P1701N2600N	●
27	0/-0.033	3	305	460	1	P1701N2700N	▲
28	0/-0.033	3	305	460	1	P1701N2800N	▲
29	0/-0.033	3	305	460	1	P1701N2900N	○
30	0/-0.033	3	305	460	1	P1701N3000N	●

★ 1st choice, ☆ suitable, ● stock standard, ● non-stock standard (no MOQ), ○ non-stock standard (MOQ), ▲ upcoming product, ▽ stock exhaustion

SOLID

H - CARBIDE DRILLS

I - HSS DRILLS

J - CARBIDE END MILLS

K - HSS END MILLS

L - CARBIDE BURRS